




## **PURI**

spot for 240V 3-phase track, QPAR51, matt black, max. 50W, incl. 3-phase adapter

Adjustable high-voltage spot PURI with suitable adapter for the 240V 3-phase track system. The luminaire is made of aluminium and, thanks to the GU10 socket, is suitable for both halogen and LED lamps. A deco ring is included to place on the lamp for halogen lamps with 5 cm diameter.



## **TECHNICAL DATA**

Socket         GU10           Lamp         QPAR51           Number of sockets         1           Lamps included         0           Primary nominal voltage         220-240V ~50/60Hz mA/V           Tilt range         85 °           Horizontal rotation range         350 °           Length         8.4 cm           Height         9.9 cm           Diameter         3.6 cm           Net weight         0.177 kg           Gross weight         0.229 kg           IP Code         IP 20           Safety class         II           Assembly         Surface           Assembly details         Ceiling,Track Ceiling,Track Wall,Wall           Wattage         50 W           Color         black	Item no.:	153560		
Number of sockets  Lamps included  Primary nominal voltage  220-240V ~50/60Hz mA/V  Tilt range  85 °  Horizontal rotation range  250 °  Length  8.4 cm  Height  9.9 cm  Diameter  3.6 cm  Net weight  0.177 kg  Gross weight  IP Code  IP 20  Safety class  II  Assembly  Assembly details  Ceiling, Track Ceiling, Track Wall, Wall  Wattage	Socket	GU10		
Lamps included  Primary nominal voltage  220-240V ~50/60Hz mAVV  Tilt range  85 °  Horizontal rotation range  350 °  Length  8.4 cm  Height  9.9 cm  Diameter  3.6 cm  Net weight  0.177 kg  Gross weight  1P Code  IP 20  Safety class  II  Assembly  Assembly  Surface  Ceiling, Track Ceiling, Track Wall, Wall  Wattage	Lamp	QPAR51		
Primary nominal voltage  220-240V ~50/60Hz mA/V  Tilt range  85 °  Horizontal rotation range  350 °  Length  8.4 cm  Height  9.9 cm  Diameter  3.6 cm  Net weight  0.177 kg  Gross weight  1P Code  IP 20  Safety class  II  Assembly  Assembly details  Ceiling, Track Ceiling, Track Wall, Wall  Wattage	Number of sockets	1		
Tilt range 85 ° Horizontal rotation range 350 °  Length 8.4 cm  Height 9.9 cm  Diameter 3.6 cm  Net weight 0.177 kg  Gross weight 0.229 kg  IP Code IP 20  Safety class II  Assembly Surface  Assembly details Ceiling, Track Wall, Wall  Wattage 50 W	Lamps included	0		
Horizontal rotation range 350 °  Length 8.4 cm  Height 9.9 cm  Diameter 3.6 cm  Net weight 0.177 kg  Gross weight 0.229 kg  IP Code IP 20  Safety class II  Assembly Surface  Assembly details Ceiling, Track Ceiling, Track Wall, Wall  Wattage 50 W	Primary nominal voltage	220-240V ~50/60Hz mA/V		
Length 8.4 cm  Height 9.9 cm  Diameter 3.6 cm  Net weight 0.177 kg  Gross weight 0.229 kg  IP Code IP 20  Safety class II  Assembly Surface  Assembly details Ceiling, Track Ceiling, Track Wall, Wall  Wattage 50 W	Tilt range	85 °		
Height 9.9 cm  Diameter 3.6 cm  Net weight 0.177 kg  Gross weight 0.229 kg  IP Code IP 20  Safety class II  Assembly Surface  Assembly details Ceiling, Track Ceiling, Track Wall, Wall  Wattage 50 W	Horizontal rotation range	350 °		
Diameter 3.6 cm  Net weight 0.177 kg  Gross weight 0.229 kg  IP Code IP 20  Safety class II  Assembly Surface  Assembly details Ceiling, Track Wall, Wall  Wattage 50 W	Length	8.4 cm		
Net weight       0.177 kg         Gross weight       0.229 kg         IP Code       IP 20         Safety class       II         Assembly       Surface         Assembly details       Ceiling,Track Ceiling,Track Wall,Wall         Wattage       50 W	Height	9.9 cm		
Gross weight  IP Code  IP 20  Safety class  II  Assembly  Surface  Assembly details  Ceiling,Track Ceiling,Track Wall,Wall  Wattage  50 W	Diameter	3.6 cm		
IP Code IP 20 Safety class II Assembly Surface Assembly details Ceiling,Track Ceiling,Track Wall,Wall Wattage 50 W	Net weight	0.177 kg		
Safety class  II  Assembly  Surface  Assembly details  Ceiling, Track Ceiling, Track Wall, Wall  Wattage  50 W	Gross weight	0.229 kg		
Assembly Surface  Assembly details Ceiling, Track Ceiling, Track Wall, Wall  Wattage 50 W	IP Code	IP 20		
Assembly details  Ceiling, Track Ceiling, Track Wall, Wall  Wattage  50 W	Safety class	II		
Wattage 50 W	Assembly	Surface		
	Assembly details	Ceiling, Track Ceiling, Track Wall, Wall		
Color black	Wattage	50 W		
	Color	black		
BIG WHITE Page 484	BIG WHITE Page	484		



## Recommended lamp

LED QPAR51 , lightbulb GU10 2700K°
LED QPAR51 , lightbulb GU10 300K 36°
LED QPAR51 , lightbulb GU10 4000K 36°
LED lightbulb QPAR51 , GU10, 4000K, grey

Notes			