




PURI spot for 240V 3-phase track

QPAR51, silver-grey, max. 50W, incl. 3-phase adapter

Adjustable high-voltage spot PURI with suitable adapter for the 240V 3-phase track system. The luminaire is made of aluminium and, thanks to the GU10 socket, is suitable for both halogen and LED lamps. A deco ring is included to place on the lamp for halogen lamps with 5 cm diameter.



TECHNICAL DATA

| Item no.: | 153564 | | |
|---------------------------|------------------------------------------|--|--|
| Socket | GU10 | | |
| Lamp | QPAR51 | | |
| Number of sockets | 1 | | |
| Lamps included | 0 | | |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V | | |
| Tilt range | 85 ° | | |
| Horizontal rotation range | 350 ° | | |
| Length | 8.4 cm | | |
| Height | 9.9 cm | | |
| Diameter | 3.6 cm | | |
| Net weight | 0.173 kg | | |
| Gross weight | 0.233 kg | | |
| IP Code | IP 20 | | |
| Safety class | II | | |
| Assembly | Surface | | |
| Assembly details | Ceiling, Track Ceiling, Track Wall, Wall | | |
| Wattage | 50 W | | |
| Color | grey | | |
| BIG WHITE Page | 484 | | |
| | | | |



Recommended lamp

| LED QPAR51 , lightbulb GU10 2700K° |
|------------------------------------------|
| LED QPAR51 , lightbulb GU10 300K 36° |
| LED QPAR51 , lightbulb GU10 4000K 36° |
| LED lightbulb QPAR51 , GU10, 4000K, grey |
| |

| Notes | | | |
|-------|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |