


Facade luminaire

5905339224439









C€ERE

Kanlux ZEW luminaires are a perfect solution for illuminating facades of buildings of various types, while the light flux directed both upwards and downwards, they create one beautiful decorative light accents on the façade. Owing to the high class of tightness (IP44), the luminaires can be mounted in places directly exposed to weather conditions.

GENERAL DATA:

Colour: grey Place of assembly: wall mounted Place of application: Indoors and outdoors Minimum distance from the illuminated object: 0,5m Replaceable light source: yes Light source included: no Fixture lighting direction: up and down Length [mm]: 110 Width [mm]: 65 Height [mm]: 235

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50/60 Maximum power [W]: 2 x max 35 Class of protection against electric shock: 1 Light source: PAR16 Cap: GU10 Ambient temperature range to which the product can be exposed: -20÷35 The fixture is adapted to the light sources of the following energy classes: A++,A+,A,B,C,D,E Enclosure material: aluminum alloy Protective glass material: Tempered glass Connection type: Bolt terminal block Range of sections of wires used [mm²]: 1÷2,5 IP class: 44


LOGISTIC DATA:

Unit of measurement: unit Packaging method: 12 Number of units in the secondary packaging: 1 Number of units in the packaging: 12 Net unit weight [g]: 890 Grammage [g]: 1036.67 Length of a unit pack [cm]: 11.5 Width of a unit pack [cm]: 11.5





Facade luminaire



Height of a unit pack [cm]: 24.5 Weight of a cardboard box [kg]: 12.44004 Width of a cardboard box [cm]: 25 Height of a cardboard box [cm]: 53 Length of a cardboard box [cm] : 36 Volume of a cardboard box [m³]: 0.0477



