

70523 MILO 7040T/P

Bulkhead fixture


5905339705235













Kanlux MILO is a classic channel luminaire used usually in technical rooms, garages, basements, staircases, corridors, etc. The luminaire has a metal (7040T) or plactic (7040T/P) protective mesh which protects the shade from mechanical damage.

GENERAL DATA:

Colour: grey

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m

Replaceable light source: yes

Length [mm]: 165 Width [mm]: 100 Height [mm]: 110

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50/60 Maximum power [W]: max 60

Class of protection against electric shock: ||

Lampshade material: glass Light source: GLS/CFL/LED

Cap: E27

The fixture is adapted to the light sources of the

following energy classes: A++,A+,A,B,C,D,E

Enclosure material: plastic **Connection type**: Terminal block

Range of sections of wires used [mm²]: 1-1,5

IK class: 06 IP class: 54

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 12

Number of units in the packaging: 12

Net unit weight [g]: 410 Grammage [g]: 441.67

Length of a unit pack [cm]: 18 Width of a unit pack [cm]: 13 Height of a unit pack [cm]: 12


Weight of a cardboard box [kg]: 5.30004 Width of a cardboard box [cm]: 18 Height of a cardboard box [cm]: 35 Length of a cardboard box [cm]: 48






70523 MILO 7040T/P

Bulkhead fixture





Volume of a cardboard box [m³]: 0.03024



Oprawa: KANLUX S.A. (kat 70523) MILO 7040T P Lampy: 1 x A60 60W/c

