


## Ceiling-mounted spotlight fitting

5905339259950







Kanlux VIDI is a family of simple in their form, diverse spotbeam holders. You can compose diverse lighting sets of them, choosing from among many colours of these aluminium holders.

#### **GENERAL DATA:**

Colour: black matt Necessity of using self-shielding lamps: yes Place of assembly: Recessed mount in the ceiling Place of application: Indoors Minimum distance from the illuminated object: 0,5m Replaceable light source: yes The product is not suitable to be installed on a normally flammable surface: >35W The product is not suitable to be covered with a heatinsulating material: yes Light source included: no Height [mm]: 25 Diameter [mm]: 79 Assembly hole [mm]: Ø60-75 Wire length [m]: 0.12

### TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC Maximum power [W]: max 50 Class of protection against electric shock: III Light source: MR16 Cap: Gx5,3 Ambient temperature range to which the product can be exposed: 5÷25 The fixture is adapted to the light sources of the following energy classes: A++,A+,A,B,C,D,E Enclosure material: aluminum alloy Connection type: Free cable ends Wire diameter [mm<sup>2</sup>]: 0.75 Lighting-fixture angle regulation: none IP class: 20


### LOGISTIC DATA:

Unit of measurement: unit Packaging method: 50 Number of units in the secondary packaging: 1 Number of units in the packaging: 50 Net unit weight [g]: 38 Grammage [g]: 63.8 Length of a unit pack [cm]: 8.5





# Ceiling-mounted spotlight fitting



Width of a unit pack [cm]: 4.5 Height of a unit pack [cm]: 8.5 Weight of a cardboard box [kg]: 3.19 Width of a cardboard box [cm]: 24 Height of a cardboard box [cm]: 20 Length of a cardboard box [cm] : 44 Volume of a cardboard box [m<sup>3</sup>]: 0.02112



