

26773 AVAR 6262 40W-NW

LED lighting frame

5905339267733














Date of issue: 26.06.2020, 21:55



LED panels are very popular lighting elements in office interiors. Due to their durability, energy efficiency and aesthetics, they have replaced extent raster luminaires to a large. Kanlux AVAR LED is a new dimension in LED panels distinguished by modern technology and the shape of frame which emits intense and impressive light.

GENERAL DATA:

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no Replaceable light source: no

The product is not suitable to be covered with a heat-

insulating material: yes Feeder included: yes Length [mm]: 615 Width [mm]: 615 Height [mm]: 14

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50/60 Maximum power [W]: 40

Class of protection against electric shock: ||

Lampshade material: plastic
Diode type: LED SMD
Luminous flux [lm]: 3600
Colour temperature: white

Colour temperature: White Colour temperature [K]: 4000 Colour uniformity [SDCM]: ≤6 Colour-rendering index Ra: ≥80

Service life [h]: 25000

Number of on/off cycles: ≥15000

Lighting angle [°]: 110

Luminous efficiency of the lamp [lm/W]: 90

Ambient temperature range to which the product can be

exposed: 5÷25 Shade type: opal

Enclosure material: aluminum alloy Panel/frame material: aluminum alloy Connection type: Terminal block

Range of sections of wires used [mm²]: 0,75





26773 AVAR 6262 40W-NW

LED lighting frame



The fixture set includes built-in LED's with the following

energy classes: A++,A+,ALamp-heating time [s]: ≤ 1 Lamp-ignition time [s]: ≤ 0.5

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 10

Number of units in the secondary packaging: 1

Number of units in the packaging: 10

Net unit weight [g]: 490 Grammage [g]: 871

Length of a unit pack [cm]: 64 Width of a unit pack [cm]: 3 Height of a unit pack [cm]: 64 Weight of a cardboard box [kg]: 8.71

Width of a cardboard box [cm]: 32.5
Height of a cardboard box [cm]: 66.5
Length of a cardboard box [cm]: 65.5
Volume of a cardboard box [m³]: 0.141562

ADDITIONAL INFORMATION:

 AVAR 62x62 is intended for an alternative size of ceiling systems (625mmx625mm)









26773 AVAR 6262 40W-NW

LED lighting frame



Luminaire: KANLUX S.A. (kat 26773) AVAR 6262 40W-NW Lamps: 1 x AVAR 6262 40W-NW




ACCESSORIES:

28512 AVAR DALI SET 40W



Set containing accessories and a power supply unit enabling communication in line with DALI protocol (28512)



We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.

