

26463 TAXI SMD P C/M-NW


Recessed light fitting

5905339264633











Kanlux TAXI SMD is a LED accent luminaire. It can be installed both indoors and outdoors (IP54). A perfect choice for decorative lighting of stairs and platforms.

GENERAL DATA:

Colour: chrome matte

Place of assembly: Recessed mount in the wall **Place of application**: Indoors and outdoors

Minimum distance from the illuminated object: 0,1m

Compatible with a dimmer: no Replaceable light source: no

Length [mm]: 110 Width [mm]: 50 Height [mm]: 44 Wire length [m]: 0.22

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50/60 Maximum power [W]: 0.6

Class of protection against electric shock: |

Diode type: LED SMD Luminous flux [lm]: 10 Colour temperature: white Colour temperature [K]: 4000 Colour uniformity [SDCM]: ≤6 Colour-rendering index Ra: ≥80

Service life [h]: 20000

Number of on/off cycles: ≥10000

Luminous efficiency of the lamp [lm/W]: 17

Ambient temperature range to which the product can be

exposed: -20÷35

Enclosure material: Metal

Panel/frame material: stainless steel Protective glass material: glass Connection type: Free cable ends Wire diameter [mm²]: 0.75

The fixture set includes built-in LED's with the following

energy classes: A++,A+,ALamp-heating time [s]: ≤ 1 Lamp-ignition time [s]: ≤ 0.5

IP class: 54


LOGISTIC DATA:





26463 TAXI SMD P C/M-NW

Recessed light fitting





Unit of measurement: unit Packaging method: 10

Number of units in the secondary packaging: ${f 10}$

Number of units in the packaging: 40

Net unit weight [g]: 204 Grammage [g]: 251.75

Length of a unit pack [cm]: 12.5 Width of a unit pack [cm]: 5.5 Height of a unit pack [cm]: 7

Weight of a cardboard box [kg]: 10.07 Width of a cardboard box [cm]: 29 Height of a cardboard box [cm]: 34 Length of a cardboard box [cm]: 31 Volume of a cardboard box [m³]: 0.030566

