




Ceiling-mounted LED light fitting

5905339333407



Kanlux BENO luminaries that's unique design and unique light effect. They were created on the basis of individual order of Kanlux, and their designs were registered by us at the patent office. Kanlux BENO LED also provides high weather resistance (IP54), quick and easy installation on the ceiling or wall, and Beno is equipped with the adjustable movement sensor. Kanlux BENO LED is a multifunctional fitting, which due to its design and its technical aspects, we can apply practically anywhere.

### GENERAL DATA:

**Colour:** white  
**Place of assembly:** wall mounted, ceiling mounted  
**Place of application:** Indoors and outdoors  
**Minimum distance from the illuminated object:** 0,5m  
**Compatible with a dimmer:** no  
**Replaceable light source:** no  
**Height [mm]:** 55  
**Diameter [mm]:** 260  
**Integrated LED light source:** yes

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC  
**Rated frequency [Hz]:** 50  
**Maximum power [W]:** 24  
**Class of protection against electric shock:** II  
**Lampshade material:** plastic  
**Diode type:** LED SMD  
**Luminous flux [lm]:** 2060  
**Colour temperature:** white  
**Colour temperature [K]:** 4000  
**Colour uniformity [SDCM]:** ≤6  
**Colour-rendering index Ra:** ≥80  
**Service life [h]:** 20000  
**Number of on/off cycles:** ≥20000  
**Lighting angle [°]:** 110  
**Luminous efficiency of the lamp [lm/W]:** 86  
**Ambient temperature range to which the product can be exposed:** -15÷35  
**Enclosure material:** plastic  
**Connection type:** Self-clamping block  
**Range of sections of wires used [mm<sup>2</sup>]:** 0,5÷1,5  
**The fixture set includes built-in LED's with the following energy classes:** A++,A+,A  
**Lamp-heating time [s]:** ≤1  
**Lamp-ignition time [s]:** ≤0,5

## 33340 BENO 24W NW-O-W

Ceiling-mounted LED light fitting



**IP class:** 54

### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 10

**Number of units in the secondary packaging:** 1

**Number of units in the packaging:** 10