

27117 TP SLIM TW LED 40W-NW

Linear LED luminaire

5905339271174
















Kanlux TP SLIM TW is a small hermetic luminaire that can be wall or ceiling mounted. Convenient assembly is ensured by adjustable clamps and quick connect fittings, which are included in the luminaire. The IP rating of IP65 and the IK rating of IK 08 allow the luminaire to be used in industrial rooms, warehouses, car parks, and garages. In addition, Kanlux TP SLIM TW luminaires can be connected into lines. Twelve and ten luminaires can be connected for 40W and 50W versions respectively.

GENERAL DATA:

Colour: white

Place of assembly: wall mounted, ceiling mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m Possibility of fixture-loop-through connection: yes

Compatible with a dimmer: no Replaceable light source: no Fixture lighting direction: down

Length [mm]: 1235 Width [mm]: 35 Height [mm]: 55

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: 40

Class of protection against electric shock: ||

Lampshade material: plastic

Diode type: LED SMD
Luminous flux [Im]: 4400
Colour temperature: white
Colour temperature [K]: 4000
Colour uniformity [SDCM]: ≤6
Colour-rendering index Ra: ≥80

Service life [h]: 25000

Number of on/off cycles: ≥20000 Lighting angle [°]: X145/Y110

Luminous efficiency of the lamp [lm/W]: 110

Ambient temperature range to which the product can be

exposed: -20÷40

Enclosure material: plastic

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 1,5-2,5

Date of issue: 08.07.2020, 09:03

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





27117 TP SLIM TW LED 40W-NW

Linear LED luminaire

The fixture set includes built-in LED's with the following

energy classes: A++,A+,A Lamp-heating time [s]: <1 Lamp-ignition time [s]: ≤0,5

Maximum number of loop-through-connected fixtures: 12

IK class: 08 IP class: 65

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 12

Number of units in the packaging: 12

Net unit weight [g]: 640 Grammage [g]: 745.83

Length of a unit pack [cm]: 131.5 Width of a unit pack [cm]: 5.5 Height of a unit pack [cm]: 4

Weight of a cardboard box [kg]: 8.94996 Width of a cardboard box [cm]: 17 Height of a cardboard box [cm]: 18 Length of a cardboard box [cm]: 135 Volume of a cardboard box [m³]: 0.04131

