

Recessed-mounted LED panel

5905339331823



ACCESSORIES	index	BLINGO LED				
		BLINGO P 38W 6060 NW	BLINGO R 38W 12030 NW	BLINGO R 38W 6060 NW	BLINGO RU 38W 6060 NW	BLINGO TU 48W 6060 NW
		33180	29823	29822	29824	29825
ADTR-H 6060 B	29845	✓		✓	✓	
ADTR-H 6060 SR	29844	✓		✓	✓	
ADTR-H 6060 W	29843	✓		✓	✓	
ADTR-H 12030 B	33391		✓			
ADTR-H 12030 SR	33392		✓			
ADTR-H 12030 W	33390		✓			
ADTR-H 76MM 6060 B (on individual order only)	33396					✓
ADTR-H 76MM 6060 SR (on individual order only)	33397					✓
ADTR-H 76MM 6060 W (on individual order only)	33398					✓
CLIPS BLINGO RT	29826	✓	✓	✓	✓	✓
SPN BRAVO S/P 60-62	28504	✓	✓	✓	✓	✓



In Kanlux BLINGO panels, the LED modules are located on the rear panel wall and light directly downwards. These are backlit panels equipped with lenses that extend the angle of light emission, ensuring the uniformity of illumination. Elimination of the light-conducting plate greatly reduces the possibility of the luminaire yellowing and allows for better light parameters. We also provide a whole range of accessories for Kanlux BLINGO panels.

GENERAL DATA:

Colour: white
Place of assembly: Recessed mount in the ceiling
Place of application: Indoors
Minimum distance from the illuminated object: 0,5m
Compatible with a dimmer: no
Replaceable light source: no
The product is not suitable to be covered with a heat-insulating material: yes
Feeder included: yes
Length [mm]: 595
Width [mm]: 595
Height [mm]: 35
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 38
Class of protection against electric shock: II
Lampshade material: plastic
Diode type: LED SMD
Luminous flux [lm]: 3800
Colour temperature: cold white
Colour temperature [K]: 6500
Colour uniformity [SDCM]: ≤6
Colour-rendering index Ra: ≥80
Service life [h]: 50000
Number of on/off cycles: ≥30000
Lighting angle [°]: 120
Luminous efficiency of the lamp [lm/W]: 100
Ambient temperature range to which the product can be exposed: 5÷25
Enclosure material: steel
Panel/frame material: steel
Connection type: Terminal block

33182 BLINGO R 38W 6060 CW

Recessed-mounted LED panel

Power-supply type: direct current

The fixture set includes built-in LED's with the following energy classes: A++,A+,A

Lamp-heating time [s]: ≤1

Lamp-ignition time [s]: ≤0,5

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 5

Number of units in the secondary packaging: 1

Number of units in the packaging: 5

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website