

33181 BLINGO IPR 38W 6060NW

Recessed-mounted LED panel



5905339331816



IP
44/20

HIGH
~100 lm/W

5
WARRANTY
5 years



GENERAL DATA:

Colour: white

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

Replaceable light source: no

The product is not suitable to be covered with a heat-insulating material: yes

Feeder included: yes

Length [mm]: 595

Width [mm]: 595

Height [mm]: 35

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: 38

Class of protection against electric shock: II

Lampshade material: plastic

Diode type: LED SMD

Luminous flux [lm]: 3800

Colour temperature: white

Colour temperature [K]: 4000

Colour uniformity [SDCM]: ≤6

Colour-rendering index Ra: ≥80

Service life [h]: 50000

Number of on/off cycles: ≥30000

Lighting angle [°]: 120

Luminous efficiency of the lamp [lm/W]: 100

Ambient temperature range to which the product can be exposed: 5÷25

Enclosure material: steel

Panel/frame material: steel

Connection type: Terminal block

Power-supply type: direct current

The fixture set includes built-in LED's with the following energy classes: A++,A+,A

Lamp-heating time [s]: ≤1

Lamp-ignition time [s]: ≤0,5

IP class: 44/20

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 5

Number of units in the secondary packaging: 1

Number of units in the packaging: 5

Net unit weight [g]: 1550

33181 BLINGO IPR 38W 6060NW

Recessed-mounted LED panel

Grammage [g]: 2302

Length of a unit pack [cm]: 62

Width of a unit pack [cm]: 4.5

Height of a unit pack [cm]: 68

Weight of a cardboard box [kg]: 11.51

Width of a cardboard box [cm]: 26

Height of a cardboard box [cm]: 70

Length of a cardboard box [cm] : 65

Volume of a cardboard box [m³]: 0.1183

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website