

29241 SANI IP44 DSO-W

Ceiling-mounted spotlight fitting

5905339292414



















KANLUX SANI IP44 are surface holders. They are characterized by simple stylistics and availability in two colours - white and black. High tightness of the holders (IP44) allows using them in rooms where electric devices are exposed to increased humidity and risk of flooding with water e.g. bathroom and kitchen.

GENERAL DATA:

Colour: white

Place of assembly: ceiling mounted Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Replaceable light source: yes

The product is not suitable to be covered with a heat-

insulating material: yes Light source included: no Height [mm]: 95

Height [mm]: 95 Diameter [mm]: 80

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50/60 Maximum power [W]: max 10

Class of protection against electric shock: |

Lampshade material: plastic

Light source: PAR16

Cap: GU10

Ambient temperature range to which the product can be

exposed: 5÷25

The fixture is adapted to the light sources of the

following energy classes: A++,A+,A **Enclosure material**: aluminum alloy **Connection type**: Bolt terminal block

Range of sections of wires used [mm 2]: $0.75 \div 1.5$

IP class: 44

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 20

Number of units in the secondary packaging: 1

Number of units in the packaging: 20

Net unit weight [g]: 280 Grammage [g]: 334

Length of a unit pack [cm]: 9 Width of a unit pack [cm]: 9 Height of a unit pack [cm]: 10.5



We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





29241 SANI IP44 DSO-W

Ceiling-mounted spotlight fitting



Weight of a cardboard box [kg]: 6.68
Width of a cardboard box [cm]: 19.5
Height of a cardboard box [cm]: 23
Length of a cardboard box [cm]: 45
Volume of a cardboard box [m³]: 0.020183

ADDITIONAL INFORMATION:

• Luminaire only for LED source.



Photometry: the results obtained from testing were from a specific sample.