Kanlux 07173 BERG DL-10L


In-ground lighting fitting 5905339071736











Kanlux BERG is a durable ground-recessed luminaire using a replaceable light source with an GU10 screw. It works great in illumination of driveways, alleys, sidewalks etc. It is manufactured of best quality materials owing to which can resist pressure up to 2 tons.

GENERAL DATA:

Colour: stainless steel Place of assembly: mounted on the ground, in-ground Place of application: Indoors and outdoors Minimum distance from the illuminated object: 0,5m Possibility of fixture-loop-through connection: yes Replaceable light source: yes Light source included: no Fixture lighting direction: Top Length [mm]: 110 Width [mm]: 110 Height [mm]: 145 Number of chokes: 2

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 10 Class of protection against electric shock: | Light source: PAR16 LED Cap: GU10 Ambient temperature range to which the product can be **exposed**: -20÷35 The fixture is adapted to the light sources of the following energy classes: A++,A+,A,B,C,D,E Enclosure material: steel Panel/frame material: stainless steel Protective glass material: Tempered glass **Connection type**: Bolt terminal block Range of sections of wires used [mm²]: 1÷2,5 Permissible static pressure [kN]: 20 **IK class: 08 IP class:** 67

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 20 Number of units in the secondary packaging: 1 Number of units in the packaging: 20 Net unit weight [g]: 842 Grammage [g]: 942 Length of a unit pack [cm]: 11.5



In-ground lighting fitting



Width of a unit pack [cm]: 11.5 Height of a unit pack [cm]: 16 Weight of a cardboard box [kg]: 18.84 Width of a cardboard box [cm]: 25 Height of a cardboard box [cm]: 33.5 Length of a cardboard box [cm] : 60.5 Volume of a cardboard box [m³]: 0.050669

ADDITIONAL INFORMATION:

- Junction box included
- optional pass-through connection of light fixtures
- easier light source replacement