


## **DASAR® 270**

## Outdoor LED inground fitting, 4000K, round, IP67, symmetrical beam

Are you looking for an inground fitting for open spaces or lights for your garden pond? If so, our DASAR® 270 would be the best choice. It is protected from penetration by dust and water (even if it is occasionally submerged). With its IP 65 / IP 67 safety class, we ensure that you will have great illumination with high light quality. You can have particularly pleasant lighting outdoors thanks to the Premium LED that is installed in the DASAR® 270 inground fitting. Of course, the lamp head is tiltable. The DASAR® 270 is a member of our SLV family, and has been developed with heart and soul. Our products are a combination of fair prices and original designs - so that your lighting project will be fantastic!



## **TECHNICAL DATA**

| Item no.:                           | 1002898                |
|-------------------------------------|------------------------|
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 700 mA/V               |
| Vertical tilting range              | 30 °                   |
| Height                              | 20.3 cm                |
| Diameter                            | 27.0 cm                |
| Installation diameter               | 25.0 cm                |
| Installation depth                  | 19.9 cm                |
| Net weight                          | 5.932 kg               |
| Gross weight                        | 6.563 kg               |
| IP Code                             | IP 65 / IP 67          |
| Safety class                        | I                      |
| Impact resistance class             | IK08                   |
| Impact resistance                   | 5 Joule                |
| Assembly                            | Recessed               |
| Assembly details                    | Ground                 |
| Number of through-wires             | 60                     |
| Wattage                             | 30 W                   |
| Lumen                               | 2600 lm                |
| Colour temperature                  | 4000 Kelvin            |
| Beam angle                          | 38 °                   |
| Color                               | black                  |
|                                     | •                      |

|   |    |       |     |   |   | 4 |   |   |   | 4 |   |   | - |    | - |   | 4 | -  | 4 | 4 | ч. | 4 | 4 | 4 | 4 | 4 |   |   |   |   |   |   |   |     |    |  |
|---|----|-------|-----|---|---|---|---|---|---|---|---|---|---|----|---|---|---|----|---|---|----|---|---|---|---|---|---|---|---|---|---|---|---|-----|----|--|
|   | 4  | - 4   | - 4 | a | J | J | J | J | a | J | J | J | J | J. | ä | ä | ä | J. |   |   |    |   |   |   |   |   |   |   |   |   |   |   |   |     |    |  |
| J | L. | . L L | ı J | J | J | J | J | J | J | J | J | J | J | J  | J | J |   | 4  |   |   | ı  |   | ı |   | 1 | ı | 1 | ı | J | ı | ı | ı | 1 | , د | 1, |  |
|   |    |       |     |   |   |   |   |   |   |   |   |   |   |    |   |   |   |    |   |   |    |   |   |   |   |   |   |   |   |   |   |   |   |     |    |  |



## Accessories

| 1002899 | Grill Diffusor for DASAR® 270 Outdoor , LED inground fitting with symmetrical beam |
|---------|--|
|---------|--|

| CRI                         | >80     |
|-----------------------------|---------|
| Binning                     | 3       |
| LXXBXX data                 | 70/50   |
| Service life                | 50000 h |
| Minimum ambient temperature | -20 °C  |
| Maximum ambient temperature | 30 °C   |
| Mechanical loading          | 2 t     |
| BIG WHITE Page              | 763     |

| Notes |  |  |
|-------|--|--|
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |
|       |  |  |