




SOMNILA FLEX

indoor LED surface-mounted wall light 3000K white version left incl. USB connection

Developed as an ideal bedside or reading light, the SOM-NILA light series provides an innovative and user-friendly luminaire concept. The elegant surface-mounted wall light is made from white or black coated aluminium and impresses with its professionally manufactured mechanics, combined with modern LED technology. Equipped with a USB connection and the necessary Smartphone holder, the luminaire provides real added value. The spotlight can be individually directed, therefore providing ideal and accurate illumination. The second light source is used for general lighting. If necessary, the two light sources of the luminaire, which are separated by the built-in switch, can be switched separately. The luminaires are available in versions for left-hand and right-hand mounting so that they can be perfectly integrated in the room. The luminaire includes built-in LED lamps.



TECHNICAL DATA

Primary nominal voltage100-240V ~50/60Hz mA/VSecondary power / secondary voltage12 mA/VWidth32.0 cmHeight40.0 cmDepth26.0 cmNet weight1.737 kgGross weight3.046 kgSafety classIAssemblySurfaceAssembly detailsWallWattage3000 KelvinBeam angle110 °ColorwhiteColorwhiteCRI>90Binning3LXXBXX data70/50Service life36000 hAmbient temperature10 °C	Item no.:	1003459
voitageWidth32.0 cmHeight40.0 cmDepth26.0 cmNet weight1.737 kgGross weight3.046 kgSafety classIAssemblySurfaceAssembly detailsWallWattage3 WLumen120 lmColour temperature3000 KelvinBeam angle110°ColorwhiteCRI>90Binning3LXXBXX data70/50Service life36000 hAmbient temperature45 °C	Primary nominal voltage	100-240V ~50/60Hz mA/V
Height40.0 cmDepth26.0 cmNet weight1.737 kgGross weight3.046 kgSafety classIAssemblySurfaceAssembly detailsWallWattage3 WLumen120 lmColour temperature3000 KelvinBeam angle110 °ColorwhiteColor3Kattage3Beam angle10 °ColorSurfaceBeam angle10 °ColorSafety classBinning3Binning3Carl36000 hService life36000 h	Secondary power / secondary voltage	12 mA/V
Depth26.0 cmNet weight1.737 kgGross weight3.046 kgSafety classIAssemblySurfaceAssembly detailsWallWattage3.000 KelvinColour temperature3000 KelvinBeam angle110°ColorwhiteCRI>90Binning3LXXBXX data70/50Service life36000 h	Width	32.0 cm
Net weight1.737 kgGross weight3.046 kgSafety classIAssemblySurfaceAssembly detailsWallWattage3 WLumen120 lmColour temperature3000 KelvinBeam angle110 °ColorwhiteCRI>90Binning3LXXBXX data70/50Service life36000 hAmbient temperature45 °C	Height	40.0 cm
Gross weight3.046 kgSafety classIAssemblySurfaceAssembly detailsWallWattage3 WLumen120 lmColour temperature3000 KelvinBeam angle110 °ColorwhiteCRI>90Binning3LXXBXX data70/50Service life36000 hAmbient temperature45 °C	Depth	26.0 cm
Safety classIAssemblySurfaceAssembly detailsWallWattage3 WLumen120 lmColour temperature3000 KelvinBeam angle110 °ColorwhiteColor3000 KelvinBinning3Binning3LXXBXX data70/50Service life36000 hAmbient temperature45 °C	Net weight	1.737 kg
AssemblySurfaceAssembly detailsWallWattage3 WLumen120 ImColour temperature3000 KelvinBeam angle110 °ColorwhiteCRI>90Binning3LXXBXX data70/50Service life36000 hAmbient temperature45 °C	Gross weight	3.046 kg
Assembly detailsWallWattage3 WLumen120 ImColour temperature3000 KelvinBeam angle110 °ColorwhiteCRI>90Binning3LXXBXX data70/50Service life36000 hAmbient temperature45 °C	Safety class	1
Wattage3 WLumen120 ImColour temperature3000 KelvinBeam angle110 °ColorwhiteCRI>90Binning3LXXBXX data70/50Service life36000 hAmbient temperature45 °C	Assembly	Surface
Lumen120 lmColour temperature3000 KelvinBeam angle110 °ColorwhiteCRI>90Binning3LXXBXX data70/50Service life36000 hAmbient temperature45 °C	Assembly details	Wall
Colour temperature3000 KelvinBeam angle110 °ColorwhiteCRI>90Binning3LXXBXX data70/50Service life36000 hAmbient temperature45 °C	Wattage	3 W
Beam angle110 °ColorwhiteCRI>90Binning3LXXBXX data70/50Service life36000 hAmbient temperature45 °C	Lumen	120 lm
ColorwhiteCRI>90Binning3LXXBXX data70/50Service life36000 hAmbient temperature45 °C	Colour temperature	3000 Kelvin
CRI >90 Binning 3 LXXBXX data 70/50 Service life 36000 h Ambient temperature 45 °C	Beam angle	110 °
Binning 3 LXXBXX data 70/50 Service life 36000 h Ambient temperature 45 °C	Color	white
LXXBXX data 70/50 Service life 36000 h Ambient temperature 45 °C	CRI	>90
Service life 36000 h Ambient temperature 45 °C	Binning	3
Ambient temperature 45 °C	LXXBXX data	70/50
	Service life	36000 h
Minimum ambient temperature -10 °C	Ambient temperature	45 °C
	Minimum ambient temperature	-10 °C



Recommended lamp

Maximum ambient temperature BIG WHITE Page 45 °C 255

1001916	VALETO® LED lamp , E27, 2700-6500K, 240°, 9W
1003090	LED lamp , A60, E27, 2700K, 810lm, 270°, dimmable, frosted glass
560402	A60 RETROFIT LED , lamp, E27, 2700K, 10W, dimmable
560422	A60 RETROFIT LED , lamp, E27, 2700K, 15W, dimmable

Notes