


Ducted fan 8594056490066









Kanlux CYKLON EOL series of fans is available in three sizes with diameter of 100, 120 and 150mm. They are made of plastic, in white colour. Their power is 19, 20 and 22W respectively. The number of rotations from each size comes to 2550/min.

GENERAL DATA:

Colour: white Place of assembly: Recessed mount in the wall Place of application: Indoors Off switch: yes Length [mm]: 162 Width [mm]: 103 Height [mm]: 150 Assembly hole [mm]: Ø120 Cable length [m]: 1.9 Wire length [m]: 1.9

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50/60 Maximum power [W]: 20 Class of protection against electric shock: II Engine rotation: 2550 Bearing type: sliding Connection type: Cable terminated with a plug Sound pressure [dB]: 38 Air-flow volume rate [m3/h]: 150 Motor-power consumption [W]: 20 IP class: X4 Protection class: II

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 12 Number of units in the packaging: 12 Net unit weight [g]: 600 Grammage [g]: 733.33 Length of a unit pack [cm]: 16 Width of a unit pack [cm]: 10.5 Height of a unit pack [cm]: 17 Weight of a cardboard box [kg]: 8.79996 Width of a cardboard box [cm]: 32 Height of a cardboard box [cm]: 33.5 Length of a cardboard box [cm]: 35 Volume of a cardboard box [m³]: 0.03752



Ducted fan

ADDITIONAL INFORMATION:

- Rotation speed: 2550/min
- Efficiency 150m3/h
- Noise level 38dB (A)
- CYKLON EOL120HT, additionally equipped with a moisture sensor which allows the fan to activate after reaching a preset moisture threshold