

07371 TESON AL-DTL50

Ceiling-mounted spotlight fitting


5905339073716













Kanlux TESON are simple eyes which will light up each room. You can choose a source of light and a version of the holder on your own - with adjustment or immovable.

GENERAL DATA:

Colour: aluminium

Necessity of using self-shielding lamps: yes **Place of assembly**: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Replaceable light source: yes

The product is not suitable to be installed on a normally

flammable surface: >35W

The product is not suitable to be covered with a heat-

insulating material: yes Light source included: no

Length [mm]: 83 Width [mm]: 83 Height [mm]: 24

Assembly hole [mm]: Ø70-75

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50/60 Maximum power [W]: max 50

Class of protection against electric shock: ||

Light source: PAR16

Cap: GU10

Ambient temperature range to which the product can be

exposed: 5÷25

The fixture is adapted to the light sources of the

following energy classes: A++,A+,A,B,C,D,E

Enclosure material: aluminum alloy **Connection type**: Bolt terminal block

Range of sections of wires used [mm²]: 0,75÷2,5 Lighting-fixture angle regulation: in one axis Lighting-fixture angle regulation [°]: 30

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 50

Number of units in the secondary packaging: 1

Number of units in the packaging: 50


Net unit weight [g]: 130





07371 TESON AL-DTL50

Ceiling-mounted spotlight fitting



Grammage [g]: 168

Weight of a cardboard box [kg]: 8.4 Width of a cardboard box [cm]: 25.5 Height of a cardboard box [cm]: 23 Length of a cardboard box [cm]: 53

Volume of a cardboard box [m³]: 0.031085

