


27411 ALIN 4LED 1X60-B

T8 LED tube linear fittings

5905339274113







GENERAL DATA:

Colour: black

Place of assembly: for suspension on the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Replaceable light source: yes Light source included: no Fixture lighting direction: down

Power supply of T8 LED fluorescent lamps: Unilateral

Length [mm]: 630 Width [mm]: 60 Height [mm]: 69

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 18

Class of protection against electric shock: |

Lampshade material: plastic

Light source: T8 LED

Cap: G13

Ambient temperature range to which the product can be

exposed: 5÷25 Shade type: matt

The fixture is adapted to the light sources of the

following energy classes: A++,A+,A Enclosure material: aluminum alloy Connection type: Self-clamping block

Range of sections of wires used [mm 2]: 1,5 \div 2,5

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 1100 Grammage [g]: 1280

Length of a unit pack [cm]: 74 Width of a unit pack [cm]: 11 Height of a unit pack [cm]: 7


Weight of a cardboard box [kg]: 1.28
Width of a cardboard box [cm]: 11
Height of a cardboard box [cm]: 7
Length of a cardboard box [cm]: 74
Volume of a cardboard box [m³]: 0.005698






27411 ALIN 4LED 1X60-B

T8 LED tube linear fittings




KANLUX S.A. (kat 27411) ALIN 4LED 1X60-B + GLASSv3 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 27411) ALIN 4LED 1X60-B + GLASSv3 Lamps: 1 x T8 LED GLASSv3 9W-NW



KANLUX S.A. (kat 27411) ALIN 4LED 1X60-B + GLASSv2 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 27411) ALIN 4LED 1X60-B + GLASSv2 Lamps: 1 x T8 LED GLASSv2 9W-WW







27411 ALIN 4LED 1X60-B

T8 LED tube linear fittings

