


## **SUPROS MOVE CL**

Indoor LED ceiling mounted light, round, white, 4000K,  $60^{\circ}$  reflector, CRI90, 3520lm

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.



## **TECHNICAL DATA**

Item no.:	1003286	
Lamps included	0	
Primary nominal voltage	220-240V ~50/60Hz mA/V	
Secondary power / secondary voltage	950 mA/V	
Vertical tilting range	50 °	
Horizontal rotation range	350 °	
Height	20.5 cm	
Diameter	12.7 cm	
Net weight	1.37 kg	
Gross weight	1.465 kg	
IP Code	IP 20	
Safety class	1	
Assembly	Surface	
Assembly details	Ceiling	
Wattage	36 W	
Lumen	3520 lm	
Colour temperature	4000 Kelvin	
Beam angle	60 °	
Color	white	
Binning	3	
LXXBXX data	70/50	
Service life	50000 h	



## Accessories

114102	REFLECTOR , for SUPROS, 20°, incl. glass and fixing ring
114104	REFLECTOR , for SUPROS, 40°, incl. glass and fixing ring

Ambient temperature	25 °C
BIG WHITE Page	325

Notes		