


## SUPROS MOVE CL

## Indoor LED ceiling mounted light, round, black, 4000K, 60° reflector, CRI90, 2700lm

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.

20,5



Ø 12,7

## **TECHNICAL DATA**

Item no.:	1003287
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	750 mA/V
Vertical tilting range	50 °
Horizontal rotation range	350 °
Height	20.5 cm
Diameter	12.7 cm
Net weight	1.37 kg
Gross weight	1.465 kg
IP Code	IP 20
Safety class	1
Assembly	Surface
Assembly details	Ceiling
Wattage	31 W
Lumen	2700 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	black
CRI	>90
Binning	3
LXXBXX data	70/50
Service life	50000 h



Ambient temperature	25 °C
BIG WHITE Page	325

## 114102 REFLECTOR , for SUPROS, 20°, incl. glass and fixing ring 114104 REFLECTOR , for SUPROS, 40°, incl. glass and fixing ring

Accessories

Notes