3~ NUMINOS® DALIS

3 phase system light white/black 3000K 24 $^{\circ}$

No two projects are the same. But many projects demand a coherent lighting and design concept. NUMINOS® is a perfectly coordinated lighting system that harmonises function, design and technology. For planners and doers, for every requirement and for maximum variety with minimum effort. From hotels and offices to commercial or private rooms. From application to technology to design in detail: the modular downlights and spotlights can be configured exactly as required by the design or spatial conditions in question. The more multifaceted your project is, the more you can benefit from the intelligent NUMINOS® lighting system. Thanks to the wide selection of modules, there is a suitable solution for every need. The NUMINOS® lighting family, which can be configured and combined, offers over a thousand possibilities. Like the 3-circuit track spotlight, with which you can adapt the lighting effect to suit the lighting context in question. With the best workmanship and light quality, which can be flexibly linked and centrally controlled thanks to the integrated LED driver (DALI dimming). This means that easy installation is a mere formality. When will you choose SLV's modular variety? Here you can find the configurator: www.NUMINOS.SLV.com

TECHNICAL DATA

Item no.:	1004374		
Primary nominal voltage	220-240V ~50/60Hz mA/V		
Secondary power / secondary voltage	250 mA/V		
Vertical tilting range	90 °		
Horizontal rotation range	350 °		
Length	16.2 cm		
Height	14.5 cm		
Diameter	6.5 cm		
Net weight	0.53 kg		
Gross weight	0.567 kg		
Safety class	I		
Assembly details	Track Ceiling, Track Wall		
Dimming technology	DALI		
Wattage	10.42 W		
Lumen	1020 lm		
Colour temperature	3000 Kelvin		
Beam angle	24°		
Color	white		
CRI	>90		
UGR≤	13		
Binning	3		
LXXBXX data	70/50		
	•		





Service life	50000 h
BIG WHITE Page	43

Notes			