


## **28456** AL 4LED 150-MPR-B

## T8 LED tube linear fittings

## 5905339284563







### **GENERAL DATA:**

Colour: black

Place of assembly: for suspension on the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Replaceable light source: yes Light source included: no Fixture lighting direction: down

Power supply of T8 LED fluorescent lamps: Unilateral

Length [mm]: 1540 Width [mm]: 60 Height [mm]: 69

## TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 58

Class of protection against electric shock: |

Lampshade material: plastic

Light source: T8 LED

Cap: G13

Ambient temperature range to which the product can be

exposed: 5÷25

Shade type: microprismatic

The fixture is adapted to the light sources of the

**following energy classes**: A++,A+,A **Enclosure material**: aluminum alloy **Connection type**: Self-clamping block

Range of sections of wires used [mm $^2$ ]: 1,5 $\div$ 2,5

IP class: 20

## LOGISTIC DATA:

Unit of measurement: unit Packaging method: 1

Number of units in the secondary packaging: 1

Number of units in the packaging: 1

Net unit weight [g]: 2180 Grammage [g]: 2630

Length of a unit pack [cm]: 182 Width of a unit pack [cm]: 11 Height of a unit pack [cm]: 7

Weight of a cardboard box [kg]: 2.63
Width of a cardboard box [cm]: 11
Height of a cardboard box [cm]: 7
Length of a cardboard box [cm]: 182
Volume of a cardboard box [m³]: 0.014014






# 28456 AL 4LED 150-MPR-B

# T8 LED tube linear fittings




#### KANLUX S.A. (kat 28456) AL 4LED 150-MPR-B + GLASSv3 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 28456) AL 4LED 150-MPR-B + GLASSv3 Lamps: 1 x T8 LED GLASSv3 24W-NW



#### KANLUX S.A. (kat 28456) AL 4LED 150-MPR-B + GLASSv2 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 28456) AL 4LED 150-MPR-8 + GLASSv2 Lamps: 1 x T8 LED GLASSv2 24W-NW







# 28456 AL 4LED 150-MPR-B

## T8 LED tube linear fittings

