


## SUPROS MOVE

## Indoor LED recessed ceiling light black round 4000K $\rm 60^{\circ}$ CRI90 2700Im

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.



## **TECHNICAL DATA**

Item no.:	1003311	
Lamps included	0	
Primary nominal voltage	220-240V ~50/60Hz mA/V	
Secondary power / secondary voltage	750 mA/V	
Vertical tilting range	60 °	
Horizontal rotation range	350 °	
Height	17.0 cm	
Diameter	19.5 cm	
Installation diameter	18.0 cm	
Installation depth	11.5 cm	
Net weight	1.516 kg	
Gross weight	1.69 kg	
IP Code	IP 20	
Safety class	11	
Assembly	Recessed	
Assembly details	Ceiling	
Wattage	31 W	
Lumen	2700 lm	
Colour temperature	4000 Kelvin	
Beam angle	60 °	
Color	black	
CRI	>90	



		Binning	3
Accessories		LXXBXX data	70/50
		Service life	50000 h
<b>114102</b> REFLECTOR , for SUPROS, 20°, incl. glass and fixing ring	Ambient temperature	25 °C	
114104		BIG WHITE Page	443
114104	REFLECTOR , for SUPROS, 40°, incl. glass and fixing ring		

Notes